

ANGEKIS

ASP-10

HD Voice Speakerphone
Portable Conference Call Speaker




New processing algorithm

360° high coverage, long pickup Upgrade full duplex technology
The 384ms echo cancellation Dynamic noise reduction.

HD conference voice

High fidelity and high reduction voice; the voice will be more clear and pure, just like taking a face to face meeting.



3D Gesture control

You can turn the microphone on and off by swiping your hand over the device.

USB HID Reverse control

HID reverse control allows synchronization of the computer volume with the microphone. Enjoy a seamless audio experience.



Portable MIC and speaker

No driver required, just plug and play. Sleek compact design fits in to all conference scenarios.

Perfect full-duplex

Two-way communication is more natural and smooth 5m voice pickup range.



ANGEKIS ASP-10

Specification

Architecture

- Tabletop console contains audio processing functions ,USB function, indicator and touch key function
 - USB cable(3m)
 - USB extend line(1.8m)
-

Dimension

- 217*206*45mm

Net Weight

- 667g

Color

- Black

Interface

- USB 2.0 (compatible with USB 3.0)
-

Microphone

- Omnidirectional microphone
 - Voice bandwidth:100-16KHz
 - Sensitivity: -38 dB
 - 94dB SPL@1KHz
 - SNR: 65dB
 - 94dB SPL@1KHz, A-weight
-

Speaker

- 3.94-inch anti-magnetic speaker
 - 4Ω5W
 - 100-24KHz
Power
 - USB supply(DC 5V / 500mA)
-

Audio

- 384ms echo cancellation
- Dynamic noise reduction
- Full duplex
- 360 degree pick-up range
- DSP audio processing

Computer system

- Windows 8 / Windows 7 / Windows 10/Windows XP,etc
 - MAC 10.7 and above
-

Function

- support computer software audio :
 - Skype
 - Slack
 - Zoom
 - Wechat/QQ
 - Whatsapp
 - Fsmeeting
 - Dingding
 - xiaoyuonline
 - etc
 - microphone mute
 - loudspeaker mute
 - volume up/down
 - Gesture control microphone on/off
 - indicator
-

Key

- microphone mute key
 - loudspeaker mute key
 - volume up/down keys
-

LED indicator

- Green: working status
- Flash in green: speaker mute
- Red: microphone mute
- Alternately blink in green and red:
- microphone and speaker are both mute

Recommended conditions

- temperature: 5°~40°
- humidity: 20~85% condensation free
- noise level: <48db
- storage temperature: -10°~40°
- Reverberation time:<0.5 seconds

Certification

- CE;FCC;CCC

Warranty

- 3 years warranty
- 1 year for battery guarantee